Nozzles




Pressure activated, automatic shut-off nozzle for full-service and self-service stations.

- XS® nozzle shuts off when:
- the pump shuts off.
- the gas tank is full.
- the lever is opened before the pump is turned on.
- the leak detector has not completed the test cycle.
- Stainless steel spout bushing keeps spout tip round and acts as a captive fastener to prevent tip-end sensor damage.
- Nozzle is equipped with a unique Flo-Stop® device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.

- StreamShaper® reduces turbulence for straighter fuel flow and less splash back spillage.
- · Comes standard with smooth full grip guard.
- · Optional EZ Lever:
- two piece design cuts opening force in half
- easier "to-the-penny" dispensing
- ADA compliant





New Unleaded Nozzles

MODEL	DESCRIPTION SHIPPING WEIGHT LBS (KG)	
159504	with Three Notch Hold Open Clip	3.1 (1.4)
E159504	with Three Notch Hold Open Clip	3.1 (1.4)
159508	w/o Hold Open Clip	3.1 (1.4)
E159508	with Hold Open Clip	3.1 (1.4)
159543	with Single Notch Hold Open Clip, Waffle Splash Guard and Flo-Equalizer	® 3.1 (1.4)
159544	with Three Notch Hold Open Clip, Waffle Splash Guard and Flo-Equalizer	3.2 (1.4)
159554	with Three Notch Hold Open Clip and Flo-Equalizer®	3.1 (1.4)
159559	with Three Notch Hold Open Clip and Waffle Splash Guard	3.0 (1.3)
159566	w/o Hold Open Clip with Waffle Splash Guard	3.0 (1.3)
159575	w/o Hold Open Clip with 1807 Waffle Splash Guard	3.0 (1.3)
159576	with Three Notch Hold Open Clip and Waffle Splash Guard	3.0 (1.3)
159582	with Three Notch Hold Open Clip and Drip Less Spout	3.0 (1.3)
159595	with Three Notch Hold Open Clip, POPD® S and Waffle Splash Guard	3.1 (1.4)
1302704	with Three Notch Hold Open Clip with GPR	3.1 (1.4)
1595106	with Two Notch Hold Open Clip	3.0 (1.3)
1595108	w/o Hold Open Clip, with POPD® S and Waffle Splash Guard	3.0 (1.3)
1595179	with One Notch Hold Open Clip and Waffle Splash Guard	3.1 (1.4)
1595224	with Two Notch Hold Open Clip, Waffle Splash Guard and Flo-Equalizer®	3.1 (1.4)
1595239	with Single Notch Hold Open Clip	3.1 (1.4)
1120559	with Two Notch Hold Open Clip, EZ Lever and Waffle Splash Guard	3.1 (1.4)
E159559	with Three Notch Hold Open Clip, Mate Guard and Waffle Splash Guard	3.1 (1.4)
		NOT LISTED

New Light Duty Diesel Nozzles

MODEL	DESCRIPTION SHIPPING WEIGHT LBS (KG)	
159503	with Three Notch Hold Open Clip	3.1 (1.4)
E159503	with Three Notch Hold Open Clip	3.1 (1.4)
E159507	w/o Hold Open Clip	3.1 (1.4)
159545	with Three Notch Hold Open Clip, Waffle Splash Guard and Flo-Equalizer®	3.2 (1.4)
159553	with Three Notch Hold Open Clip and Flo-Equalizer®	3.1 (1.4)
159557	w/o Hold Open Clip with Flo-Equalizer®	3.1 (1.4)
159561	with Three Notch Hold Open Clip and Waffle Splash Guard	3.0 (1.3)
159567	w/o Hold Open Clip with Waffle Splash Guard	3.1 (1.4)
159578	with Three Notch Hold Open Clip and Waffle Splash Guard	3.3 (1.4)
159596	with Three Notch Hold Open Clip, POPD® and Waffle Splash Guard	3.3 (1.4)
159597	with Single Notch Hold Open Clip and Waffle Splash Guard	3.1 (1.4)
1120561	with Two Notch Hold Open Clip, EZ Lever and Waffle Splash Guard	3.1 (1.4)
1595109	w/o Hold Open Clip, with POPD® S and Waffle Splash Guard	3.1 (1.4)
1595122	with Three Notch Hold Open Clip, POPD® H and Waffle Splash Guard	3.1 (1.4)
1595135	with Three Notch Hold Open Clip	3.1 (1.4)
1595211	with Three Notch Hold Open Clip, Waffle Splash Guard and Drip Less Spou	t 3.1 (1.4)
1595225	with Two Notch Hold Open Clip and Waffle Splash Guard	3.1 (1.4)
1595238	with Single Notch Hold Open Clip	3.1 (1.4)
11205109	w/o Hold Open Clip, with EZ Lever, POPD®S and Waffle Splash Guard	3.1 (1.4)
E159503N	with Three Notch Hold Open Clip and Mate Guard	3.1 (1.4)
	۸	NOT LISTED

Construction

Body	One piece die cast aluminum
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon®
Lever	Single-piece polymer lever or two-piece polymer EZ lever
Inlet	3/4" / 19.1 mm NPT











Pressure activated, automatic shut-off nozzle for full-service and self-service stations.

Dimensions and System Options

Safe-T-Breaks®

MODEL NO.	DESCRIPTION
003360	¾" F x ¾" F NPT Reconnectable Safe-T-Break®
002273	¾" F x ¾" F NPT Non-Reconnectable Safe-T-Break®
006130	¾" F x ¾" F NPT Non-Reconnectable PCC Safe-T-Break®
005230	¾" F x ¾" F NPT Low Pull Reconnectable Safe-T-Break®

Swivels

MODEL NO.	DESCRIPTION
000350	¾" M x ¾" F NPT Multi-Plane Swivel
000355	¾" M x ¾" F NPT Multi-Plane Swivel Anodized Black
002272	¾" M x ¾" F NPT 90° Pump Swivel
003895	¾" M x ¾" F NPT Inline Swivel
002950	3/4" M x 3/4" F NPT Multi-Plane Restricted Swivel

Swivel/Safe-T-Break® Combos

MODEL NO.	DESCRIPTION
006310	34" M NPT Multi-Plane Swivel connected to
	¾" F NPT Reconnectable Safe-T-Break®

Spouts

MODEL NO.	DESCRIPTION
001473	Unleaded Spout without Flo-Stop®
010434	Unleaded Long Spout without Flo-Stop®
001471	Light Duty Diesel Spout without Flo-Stop®with StreamShaper®
010353	Light Duty Diesel Long Spout without Flo-Stop®

Pressure/Vacuum Vents

MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION
004490	Conventional Flo-Equalizer® - 10 gpm / 37.9 Lpm
003593	Hold Open Clip Kit
007490	Internal Flo-Equalizer® - 10 gpm / 37.9 Lpm
007089	Nozzle Service Kit
000397	Unleaded Spout Gauge



Guards

MODEL NO.	DESCRIPTION
003376	Black Handle Guard
004145	Full Grip Guard
001806	Full Grip Reguard
005494	Lever Guard
003440	Mate Easy-on Package
003795	Mate Guard
008176	POPD® EZH Nozzle Guard
008175	POPD® EZS Nozzle Guard
007999	POPD® H Clear Cover
008185	POPD® H Full Grip Guard
008192	POPD® H Full Grip Reguard
008166	POPD® H Mate Guard
006628	POPD® S Clear Cover
006665	POPD® S Full Grip Guard
007205	POPD® S Full Grip Reguard
008165	POPD® S Mate Guard
001506	Protection Package
001809	Reguard Protection Package
001808	Waffle Splash Guard



2325 Husky Way • Pacific, MO 63069 (800) 325-3558 • Fax (636) 825-7300 www.husky.com • sales@husky.com

